

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



A.D. 1867, 31st DECEMBER. N° 3720.

Sweeping Machines.

LETTERS PATENT to Alexander Melville Clark, of 53, Chancery Lane, in the County of Middlesex, for the Invention of "IMPROVEMENTS IN ROAD SWEEPING MACHINES."—A communication from abroad by Jean Tailfer, Machinist, and Charles Léon Blot, Engineer, both of 29, Boulevard St. Martin, Paris.

Scaled the 16th June 1868, and dated the 31st December 1867.

PROVISIONAL SPECIFICATION left by the said Alexander Melville Clark at the Office of the Commissioners of Patents, with his Petition, on the 31st December 1867.

I, ALEXANDER MELVILLE CLARK, of 53, Chancery Lane, in the County of Middlesex, do hereby declare the nature of the said Invention for "IMPROVEMENTS IN ROAD SWEEPING MACHINES," to be as follows:—

This Invention relates to improvements in road sweeping machines to be driven by horse or other power.

The chief features of improvement consist, 1st, in a new mode of transmitting motion from the running wheel to the brush, which is effected direct by means of toothed gearing, dispensing with the endless chain usually employed, and simplifying the action.

2ndly. In the application of a universal joint for connecting the driving pinion to the brush axis for imparting motion thereto. In consequence of the inclined position of the brush axis with regard to the axle of the apparatus bevil gearing can only be employed in connection with an intermediate axis, but according to these improvements I use ordinary toothed gearing communicating motion direct by the aid of the universal joint, which, as before mentioned, serves to connect the pinion with the brush.

Clark's Improvements in Road Sweeping Machines.

3rdly. In a new mode of balancing the brush, whereby an elastic pressure is obtained for ensuring its perfect action.

4thly. In a new mode of regulating the sweeping action, which is effected by the aid of small wheels or rollers running on the ground fixed to the oscillating frame carrying the brush, so as to cause it to bear more or less on the ground.

I have represented one example of these improvements in road sweeping machines in the accompanying Drawings, Figure 1 of which shows a longitudinal elevation of the apparatus, Figure 2 a plan of same, while Figure 3 shows a separate view of the universal joint for connecting the driving pinion to the brush axis. The same letters of reference apply to the three Figures.

a, frame of the machine mounted on an axle *b* carrying the running wheels *c, d*, which are both mounted loosely thereon, the boss of wheel *d* being prolonged on the inside, where it is provided with a toothed wheel *f* keyed thereon and gearing with a pinion *g*; *h*, oscillating frames mounted on axle *b* carrying the ends of the brush axis; *i*, main suspension lever for regulating the action of the brush roller oscillating on the wheel axle, one end of this lever is connected to a chain *j* attached to the brush and the other end terminates in a nut, whereby the lever may be raised or lowered by means of a screw *k*; *l*, balance and pressure lever fixed at a suitable point of axle *b*, its other end resting on a spiral spring *m* carried on a stem. When the brush is lowered by the suspension lever *i* the latter comes in contact with the balance lever *l*, and by means of frame *h* and spring *m* imparts the elastic pressure desired at that end of the brush roller next the driving gear; *o*, cylindrical brush to the axis *p* of which the pinion *g* is connected by the universal joint *q*; *r*, wheels or rollers mounted on spindles *s*, so as to be readily raised or lowered according to the greater or less contact of the brush roller with the ground desired.

The Invention thus consists in the herein-described improvements in road sweeping machines, the chief features being, first, the direct transmission of motion by means of ordinary toothed gearing.

Secondly. The application of the universal joint in the manner described.

Thirdly. The new mode of balancing the brush roller, so as to obtain an elastic pressure.

Fourthly. The employment of rollers for regulating the sweeping action, as described.

Specification.

Clark

SPECIFICATION in
by the said Ale
the 25th June

TO ALL TO WH

5 MELVILLE CLARK, o
greeting.

WHEREAS Her
Patent, bearing da
Lord One thousand
10 Her reign, did, for
me, the said Alex
said Alexander Me
or such others as
administrators, and
15 from time to time
expressed, should a
the United Kingdo
and Isle of Man,
MACHINES," a comm
20 and Charles Léon I
upon the condition
Clark, my executors
or their, or one of
ascertain the nature
25 to be performed, at
Office within six ea
the said Letters Pati

NOW KNOW Y
hereby declare th
30 same is to be perfor
by the following stat
hereunto annexed, as
to say):—

This Invention re
35 driven by horse or ot
The chief feature
mitting motion from

Clark's Improvements in Road Sweeping Machines.

SPECIFICATION in pursuance of the conditions of the Letters Patent, filed by the said Alexander Melville Clark in the Great Seal Patent Office on the 25th June 1868.

TO ALL TO WHOM THESE PRESENTS SHALL COME, I, ALEXANDER
5 **MELVILLE CLARK**, of 53, Chancery Lane, in the County of Middlesex, send greeting.

WHEREAS Her most Excellent Majesty Queen Victoria, by Her Letters Patent, bearing date the Thirty-first day of December, in the year of our Lord One thousand eight hundred and sixty-seven, in the thirty-first year of
10 Her reign, did, for Herself, Her heirs and successors, give and grant unto me, the said Alexander Melville Clark, Her special licence that I, the said Alexander Melville Clark, my executors, administrators, and assigns, or such others as I, the said Alexander Melville Clark, my executors, administrators, and assigns, should at any time agree with, and no others,
15 from time to time and at all times thereafter during the term therein expressed, should and lawfully might make, use, exercise, and vend, within the United Kingdom of Great Britain and Ireland, the Channel Islands, and Isle of Man, an Invention for "**IMPROVEMENTS IN ROAD SWEEPING MACHINES**," a communication to me from abroad by Jean Tailfer, Machinist,
20 and Charles Léon Blot, Engineer, both of 29, Boulevard St. Martin, Paris, upon the condition (amongst others) that I, the said Alexander Melville Clark, my executors or administrators, by an instrument in writing under my, or their, or one of their hands and seals, should particularly describe and ascertain the nature of the said Invention, and in what manner the same was
25 to be performed, and cause the same to be filed in the Great Seal Patent Office within six calendar months next and immediately after the date of the said Letters Patent.

NOW KNOW YE; that I, the said Alexander Melville Clark, do hereby declare the nature of the said Invention, and in what manner the
30 same is to be performed, to be particularly described and ascertained in and by the following statement, reference being had to the Sheet of Drawings hereunto annexed, and to the letters and figures marked thereon (that is to say):—

This Invention relates to improvements in road sweeping machines to be
35 driven by horse or other power.

The chief features of improvement consist, 1st, in a new mode of transmitting motion from the running wheel to the brush which is effected in a

elastic pressure

which is effected
and fixed to the
more or less on 5

road sweeping
shows a longi-
while Figure 3
the driving pinion 10
three Figures.
ing the running
of wheel *d* being
wheel *f* keyed
mounted on axle *b* 15
er for regulating
e, one end of this
l th other end
ered by means of
point of axle *b*, its 20

When the brush
contact with the
aparts the elastic
the driving gear;
connected by the 25
les s, so as to be
tact of the brush

Improvements in road
ect transmission of 30

manner described.
so as to obtain an

sweeping action, as 35

Clark's Improvements in Road Sweeping Machines.

direct manner by means of spur gearing, so dispensing with the endless chain usually employed and simplifying the action.

2ndly. In the application of a universal joint connecting the driving pinion to the brush axis for imparting motion thereto. In consequence of the inclined position of the brush axis with regard to the axle of the machine bevil gearing can only be employed in connection with an intermediate axis, but according to these improvements I use ordinary spur gearing communicating motion direct by the aid of the universal joint which as before mentioned serves to connect the pinion with the brush.

3rdly. In a new mode of balancing the brush, whereby an elastic pressure is obtained for ensuring its perfect action.

4thly. In a new mode of regulating the sweeping action, which is effected by the aid of small wheels or rollers mounted on the oscillating frame carrying the brush, their position being regulated so as to make it bear more or less on the ground.

5thly. In the employment of an additional brush having a to-and-fro motion (or it may be a circular brush made to rotate) placed at the forward end of the large circular brush, serving principally when sweeping liquid mud to prevent any accumulation of mud caused by the oblique position of the large brush.

6thly. When the large brush is raised and out of action it assumes an inclined position in consequence of its being heavier at one end than the other, and to obviate this I provide a spring to keep the brush in a horizontal position.

I have represented one example of these improvements in road sweeping machines in the accompanying Drawings. Figure 1 of which shows a longitudinal elevation of the apparatus, and Figure 2 a plan of same, while Figure 3 shows a separate view of the universal joint for connecting the driving pinion to the brush axis. The same letters of reference apply to the three Figures.

a, frame of the machine mounted on an axle *b* carrying the running wheels *c*, *d*, which are both mounted loosely thereon, the boss of wheel *d* being prolonged on the inside, where it is provided with a toothed wheel *f* keyed thereon and gearing with a pinion *g*; *h*, oscillating frames mounted on axle *b* and carrying the ends of the brush axis; *i*, main suspension lever for regulating the action of the brush oscillating on the wheel axle, one end of this lever is connected to a chain *j* attached to the brush the other end terminating in a nut, whereby the lever may be raised or lowered by means of a screw *k*; *l*, balance and pressing lever fixed at a suitable point of axle *b*, its other end

16

the p

3rd

20 pressure

4thly

before d

I also

In v

25

30

35

Clark's Improvements in Road Sweeping Machines.

resting on a spiral spring *m* carried on a stem. When the brush is lowered by the suspension lever *i* the latter comes in contact with the balance lever *l*, and by means of frame *h* and spring *m* imparts the elastic pressure desired at that end of the brush next the driving gear; *a*, cylindrical brush to the axis *p* of which the pinion *g* is connected by the universal joint *q*; *r*, wheels or rollers mounted on a stem *s* so as to be readily raised or lowered according to the greater or less contact desired of the brush with the ground; *t*, additional brush for preventing the accumulation of mud produced by the oblique position of the brush; *u* spring for keeping the brush in a horizontal position when raised.

Having described the nature of this Invention, and the manner of performing the same, I declare that what I claim as the Invention to be protected by the herein-before in part recited Letters Patent as improvements in road sweeping machines is,—

1st. Transmitting motion to the brush direct by means of spur gearing, as herein-before described.

2ndly. I claim the application of the universal joint in the manner and for the purpose described.

3rdly. I claim the mode of balancing the brush so as to obtain an elastic pressure, as before described.

4thly. I claim the use of rollers for regulating the sweeping, as herein-before described.

I also reserve the right of working the apparatus by any suitable power:

In witness whereof, I, the said Alexander Melville Clark, have hereunto set my hand and seal, this Twenty-fifth day of June, in the year of our Lord One thousand eight hundred and sixty-eight.

A. M. CLARK. (L.S.)

LONDON:

Printed by GEORGE EDWARD EYRE and WILLIAM SPOTTISWOODE,
Printers to the Queen's most Excellent Majesty. 1868.

endless chain

the driving
sequence of
of the machine 5
mediate axis,
ing communi-
as before

elastic pressure 10

which is effected
frame carrying
more or less

15

and-fro motion
forward end of
liquid mud to
of the large



20

it assumes an
than the other,
a horizontal

road sweeping 25
which shows a
of same, while
connecting the
face apply to the

30

running wheels
of *d* being pro-
wheel *f* keyed
mounted on axle *b*
a lever for regu- 35
one end of this
end terminating
of a screw *k*;
t, its other end






FIG. 3.




FIG. 2.

